Quest Journals Journal of Research in Applied Mathematics Volume 8 ~ Issue 3 (2022) pp: 18-24 ISSN(Online) : 2394-0743 ISSN (Print): 2394-0735 www.questjournals.org

Research Paper



Recursive form of B-spline Based Collocation Solution to Neumann's Boundary Value problems using Matlab

Dr.Y.Rajashekhar Reddy

Assistant Professor, Department of mathematics JNT University college of Engineering Jagitial, Nachupally (kondagattu) Karimnagar-505501, Telangana State, India

Abstract: A simplified form of Recursive B-spline basis function is used as basis in collocation method. The present method is used to solve second order singular differential equations with Neumann's boundary conditions. Solutions of Numerical examples for non -uniform length of the points show the efficiency of the method and easiness. Stability of B-spline based collocation method and accuracy of numerical solution is constantly improved by decreasing the nodal space.

Keywords: Neumann's boundary conditions, Collocation method, Singular differential equations, B-splines *Received 28 Mar, 2022; Revised 06 Apr, 2022; Accepted 08 Apr, 2022* © *The author(s) 2022.*

Published with open access at www.questjournals.org

I. Introduction

In recent years, many numerical methods are developed to solve singular differential equations with Neumann- Dirchlet's boundary conditions. The methods include like B-spline collocation method [13], finite difference method [4], kernel space [5, 6] sinc collocation method [7] and predictor and corrector method [8] and many more. The B-spline based collocation method is used to evaluate boundary value problems including singular boundary value problems [9]. However, it is observed from the recent literature that B-spline basis functions are derived using fixed equidistant space for a particular degree only. If the recursive formulation given by Carl. De boor [12] is applied, the basis function evaluation can be generalized and without fixing of degree of the basis function can be used in collocation method for uniform or non uniform mesh sizes. In this paper, after defining the B-spline basis function recursively, the B-spline collocation method is described and formulated. The efficiency of the method is demonstrated using the second order singular differential

equations with Neumann's boundary conditions.

Considering second order linear differential equations with variable coefficients

$$\frac{d^2v}{dx^2} + k_1 P(x) \frac{dv}{dx} + k_2 Q(x) V = R(x) , \qquad a \le x \le b \quad \dots \quad (1)$$

with Neumann's boundary conditions $V'(a) = d1, V(b) = d2$

where a, b, d_1, d_2, k_1 and k_2 are constant P(x), Q(x) and R(x) are functions of x

Let $V^h(x) = \sum_{i=-2}^{n-1} C_i M_{i,p}(x)$ (2), where C_i 's are constants to be determined and $M_{i,p}(x)$ are B-spline basis functions, be the approximate global solution to the exact solution V(x) of the considered second order singular differential equation (1).

2.1B-splines

In this section, definition and properties of B-spline basis functions [1, 2] are given in detail. A zero degree and other than zero degree B-spline basis functions are defined at x_i recursively over the knot vector space $X = \{x_1, x_2, x_3, \dots, x_{n-1}, x_n\}$ as

i) if p=0

$$M_{i,p}(x) = 1 \qquad if \quad x \in (x_i, x_{i+i})$$

$$M_{i,p}(x) = 0 \qquad if \quad x \notin (x_i, x_{i+i})$$

$$ii) \quad if \quad p \ge 1$$

$$M_{i,p}(x) = \frac{x - x_i}{x_{i+p} - x_i} M_{i,p-1}(x) + \frac{x_{i+p+1} - x}{x_{i+p+1} - x_{i+1}} M_{i+1,p-1}(x) \qquad \dots \dots \dots (3)$$

where p is the degree of the B-spline basis function and x is the parameter belongs to X. When evaluating these functions, ratios of the form 0/0 are defined as zero



Fig (1), First degree B-spline basis function with uniform Knot vector $X = \{-1,0,1,2,3,4,5,6,7,8,9,10,11,12\}$



Fig (2), Second degree B-spline basis function with uniform Knot vector X= {-2,-1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12}

2.2 Derivatives of B-splines

If p=2, we have

$$M'_{i,p}(x) = \frac{x - x_i}{x_{i+p} - x_i} M'_{i,p-1}(x) + \frac{M_{i,p-1}(x)}{x_{i+p} - x_i} + \frac{x_{i+p+1} - x}{x_{i+p+1} - x_{i+1}} M'_{i+1,p-1}(x) - \frac{M_{i+1,p-1}(x)}{x_{i+p+1} - x_{i+1}}$$

$$M''_{i,p}(x) = 2 \frac{M'_{i,p-1}(x)}{x_{i+p} - x_i} - 2 \frac{N'_{i+1,p-1}(x)}{x_{i+p+1} - x_{i+1}}$$
.....(4)

In the above equations, previous degree functions are used as recursively to define next level degree basis function.

^{*}Corresponding Author: Dr.Y.Rajashekhar Reddy

Knot vectors are based to define the B-spline based functions. Knots are real quantities. Knot vector is a non decreasing set of Real numbers. Knot vectors are classified as non-uniform knot vectors, uniform knot vector and open uniform knot vectors. Uniform knot vector in which difference of any two consecutive knots is constant is used for test problems in this paper. Two knots are required to define the zero degree basis function .In a similar way, a pth degree B-spline basis function at a knot have a domain of influence of (p+2) knots. B-spline basis functions of degree one and degree two over uniform knot vector are shown graphically below in figures (1) and (2).



Fig (3), First derivative of second degree B-spline basis function with uniform Knot vector $X = \{-2, -1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12\}$



Fig (4), Second derivative of second degree B-spline basis function with uniform Knot vector $X=\{-2,-1, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12\}$

2.3 B-spline collocation method

Collocation method is widely used in approximation theory particularly to solve differential equations .In collocation method, the assumed approximate solution is made it exact at some nodal points by equating residue zero at that particular node. B-spline basis functions are used as the basis in B-spline collocation method whereas the base functions which are used in normal collocation method are the polynomials vanishes at the boundary values. Residue which is obtained by substituting equation (2) in equation (1) is made equal to zero at nodes in the given domain to determine unknowns in (2).Let [a,b] be the domain of the governing differential equation and is partitioned as $X = \{a = x_0, x_1, x_2, \dots, x_{n-1}, x_n = b\}$ with unequal length of *n* sub domains. The x_i 's are known as nodes, the nodes are treated as knots in collocation B-spline method where B-spline basis functions are defined and these nodes are used to make the residue equal to zero to determine unknowns C_i 's in (2).two extra knot vectors are taken into consideration beside the domain of problem both side when evaluating the second degree B-spline basis functions at the nodes.

Substuiting, the approximate solution (2) and its derivatives in (1).

$$\frac{d^2 v^h}{dx^2} + k_1 P(x) \frac{dv^h}{dx} + k_2 Q(x) V^h = R(x) \quad \text{i.e.}$$

$$\sum_{i=-2}^{n-1} C_i M''_{i,p}(x) + k_1 P(x) \sum_{i=-2}^{n-1} C_i M'_{i,p}(x) + k_2 Q(x) \sum_{i=-2}^{n-1} C_i M_{i,p}(x) = R(x)$$
...(5)

Equation (5) which is valuated at x_i 's, i=0, 1, 2,....n-1 gives the system of (n-1) × (n+1) equations in which (n+1) arbitrary constants are involved. Two more equations are needed to have (n+1) × (n+1) square matrix which helps to determine the (n+ 1) arbitrary constants. The remaining two equations are obtained using

Now using all the above equations (5), (6), (7) i.e. (n+1) a square matrix is obtained which is diagonally dominated matrix because every second degree basis function has values other than zeros only in three intervals and zeros in the remaining intervals, it is a continuing process like when one function is ending its effect in its surrounding region than other function starts its effectiveness as parameter value changing. In other words, every parameter has at most under the three (p=2) basis functions. The systems of equations are easily solved for arbitrary constants C_i's. Substuiting these constants in (2), the approximation solution is obtained and used to estimate the values at domain points.

Absolute Relative error is evaluated by using the following relationship in exact and approximate solutions

Absolute Relative Error
$$\frac{\left|\frac{M_{exact} - M_{appro}}{M_{exact}}\right|}{\left|\frac{M_{exact}}{M_{exact}}\right|}$$

3. Numerical Experiments

....

The effectiveness of the present method is demonstrated by considering the various examples

Example 1: Consider a singular boundary value problem given

$$V'' + \frac{2}{x}V' - 4V(x) = -2, 0 < x \le 1, V'(0) = 0, V(1) = 5.5$$

The exact solution $isV(x) = 0.5 + \frac{5 sinh(2x)}{x sinh 2}$. The domain is divided into unequal intervals and associated with knot vector space.

Overall behavior of B-spline collocation foe example1 solution throughout the domain is displayed in figure(5)



Fig(5), Comparison of the B-spline collocation and Exact solutions

Table 1 present's results at selected nodes inside the domain and compares their values with the exact solution for different mesh sizes. It is observed from the table1 that the solution approaches to the exact solution as the mesh size is decreased.

Node	Estimated values at	Estimated values at	Estimated values at	Exact values		
ʻx'	h=.002	h=.001	h=.0005			
.1	3.277511	3.276568	3.2760	3.2756		
.2	3.333041	3.3321818	3.33175	3.33132		
. 3	3.427204	3.4264231	3.426032	3.42564		
.4	3.562274	3.5615693	3.561216	3.560863		
.5	3.7415248	3.74089854	3.7405850	3.740271		
.6	3.9693281	3.96878741	3.9685168	3.9682461		
.7	4.2512781	4.25083626	4.25061493	4.2503932		
.8	4.5943561	4.59403112	4.59386854	4.5937058		
.9	5.0071279	5.0069472	5.00685687	5.0067664		

Table 1. Computed value and exact value at different nodes with different mesh sizes 'h'



Fig (5), Trend of maximum absolute relative error for different number of nodes

Maximum absolute relative error is approaching the x-axis as moving along the x-axis, i.e falling in values of maximum absolute relative error is happening continuously as number interpolating points are increased. This shows the consistency of the present method even close at singular points.

Example 2: The exact solution of another singular boundary value problem considered below

$$V'' + \frac{1}{x}V' = \frac{8}{(8-x^2)^2}, V'(0) = 0$$
 and $V(1) = 0$

is $V(x) = 2 \log(\frac{7}{8-x^2})$

Table 2 gives comparison of the solutions of B-spline based collocation method and Exact solution at various points. These nodes are taken at non uniform length. From table 2 approximating solution values are good fit with the values of exact solution values.

This shows the importance of this method in evaluating second order singular differential equations with Neumann's boundary conditions

Table 2. Computed value and exact value at different nodes with non uniform lengths

			-											_			0				
Node	s	0		.002	50	.123	0	.15	10	.222	25	.2590)	.3023	1	.3580		,4020		.4551	
BCS	k	-0.26	71	-0.26	570	-0.2	633	-0.2	2614	-0.2	2547	-0.25	03	-0.244	41	-0.234	8	-0.226	53	-0.21	46
Exact	t	-0.26	71	-0.26	569	-0.2	2633	-0.2	2614	-0.2	2546	-0.25	02	-0.24	41	-0.234	8	-0.226	2	-0.190	00
5014	1011																				
des	.55	00	.556	0	.621	0	.655	0	.7000)	.754	0	.82	00	.85	34	.92	210	.95	570	1

Nodes	.5500	.5500	.6210	.0550	.7000	./540	.8200	.8554	.9210	.9570	1
BCS	-0.1900	-0.2146	-0.1683	-0.1568	-0.1407	-0.1197	-0.0915	-0.0762	-0.0429	-0.0239	0.0000
Exact	-0.1900	-0.1882	-0.1683	-0.1568	-0.1407	0.1196	-0.0915	-0.0762	-0.0429	-0.0239	0
Solution											

*B-spline Collocation Solution

Overall behavior of B-spline collocation solution for eample2 throughout the domain is displayed in figure(6)



Fig (6). Comparison of approximate and Exact solutions for the Example2 for mesh size h=0.01

Conclusions

The B-spline basis functions defined recursively are incorporated in the collocation method and applied the same to the singular boundary value problems for non -uniform lengths. The effectiveness of the proposed method is illustrated by considering two numerical examples. The solution is compared with exact solution and found to be in good approximation. This method may be applied to different types of singular boundary value problems for its efficiency

References

- Hughes, T.J.R., Cottrell, J.A. and Bazilevs, Y. "Isgeometric analysis: CAD, finite elements, NURBS, exact geometry and mesh refinement", [1]. Comput. Methods Appl. Mech. Engg., 194(39–41), pp. 4135–4195 (2005). David F.Rogers and J.Alan Adams, "Mathematical Elements for Computer Graphics", 2nd ed., Tata McGraw-Hill Edition, New Delh.
- [2].
- C. de Boor and K. H"ollig. B-splines from parallelepipeds. J. Analyse Math., 42:99-15, 1982 [3].
- [4]. R.K. Pandey and Arvind K. Singh, On the convergence of a finite difference method for a class of singular boundary value problems arising in physiology, J. Comput. Appl. Math 166 (2004) 553-564.
- [5]. Geng, F.Z. and Cui, M.G. (2007) Solving Singular Nonlinear Second-Order Periodic Boundary Value Problems in the Reproducing Kernel Space. Applied Mathematics and Computation, 192, 389-398.
- Li, Z.Y., Wang, Y.L., Tan, F.G., Wan, X.H. and Nie, T.F. (2012) The Solution of a Class of Singularly Perturbed Two-Point Boundary Value [6]. Problems by the Iterative Reproducing Kernel Method. Abstract and Applied Analysis, 1-7 [7]. Mohsen, A. and El-Gamel, M. (2008) On the Galerkin and Collocation Methods for Two Point Boundary Value Problems Using Sinc Bases.
- Computers and Mathematics with Allications, 56, 930-941 Abdalkaleg Hamad, M. Tadi, Miloje Radenkovic (2014) A Numerical Method for Singular Boundary-Value Problems. Journal of Applied [8].
- Mathematics and Physics, 2, 882-887. [9]. S Joan Goh_, Ahmad Abd. Majid, Ahmad Izani Md. Ismail (2011) Extended cubic uniform B-spline for a class of singular boundary value problems.
- Science Asia 37 (2011): 79-82 I. J. SCHOENBERG Contributions to the problem of approximation of equidistant data by analytic functions, Quart. Appl. Math. 4 (1946), 45-99; [10].
- 112-141 [11]. H. B. CURRYA ND I. J. SCHOENBERG On Polya frequency functions IV: The fundamental spline functions and their limits, J. Anal. Math. 17
- (1966), 71-107. CARL DE BOOR On Calculating with B-plines. JOURNALO F APPROXIMATION THEORY 6, SO-62 (1972) [12].
- [13]. Hikmet Caglar, Nazan Caglar, Khaled Elfaituri (2006). B-spline interpolation compared with finite difference, finite element and finite volume methods which applied to twopoint boundary value problems. Applied Mathematics and Computation 175 (2006) 72-79